

Compact Track Loaders / T750 Compact Track Loader

Specifications & Options

■ Standard
 Optional
N/A Not Applicable

Units Metric

Configuration	Bobcat T750	
	Standard	Roller Suspension Option
Engine		
Emissions Tier (EPA)		Tier 4
Engine Cooling		Liquid
Engine Fuel		Diesel
Horsepower		63,4 kW
Turbocharged Engine		<input checked="" type="checkbox"/>

⊖ Performance

Rated Operating Capacity (SAE)	1508 kg
Operating Capacity (50% of Tip)	2155 kg
Tipping Load	4309 kg
Operating Weight	4747 kg
Travel Speed	10.6 km/h
Travel Speed (2-speed option)	17.2 km/h
Ground Pressure (Rubber)	0.29 bar

⊖ Capacities

Fuel Tank	166.2 l
-----------	---------

⊖ Hydraulic System

System Relief @ Quick Couplers	241,32 bar
Auxiliary Std Flow	87,1 l/min
Auxiliary High Flow	138,5 l/min

⊖ Dimension

Length	3597 mm
Length without Attachment	2903 mm
Length with Standard Bucket	3597 mm
Width	1981 mm
Width (with bucket)	2032 mm
Height	2065 mm
Height with Operator Cab	2065 mm
Height to Bucket Hinge Pin	3353 mm
Reach @ Maximum Height	853 mm
Turning Radius	2235 mm
Length of track on ground	1618 mm
Track Width	450 mm

⊖ Features

Joystick Control	<input checked="" type="checkbox"/>
Air Conditioning	<input checked="" type="checkbox"/>
Backup Alarm	<input type="checkbox"/>
BICS System (Interlock)	<input type="checkbox"/>
Cab Heater	<input checked="" type="checkbox"/>
Operating Lights	<input type="checkbox"/>
Suspension Seat	<input type="checkbox"/>
Two Speed Travel	<input checked="" type="checkbox"/>
Deluxe Instrumentation	<input checked="" type="checkbox"/>
Engine Shutdown	<input type="checkbox"/>
Hydraulic Bucket Positioning	<input checked="" type="checkbox"/>
High Flow Option	<input checked="" type="checkbox"/>
Auxiliary Hydraulics	<input type="checkbox"/>
Bob-Tach Attachment System	<input type="checkbox"/>
Power Bob-Tach	<input checked="" type="checkbox"/>
ACS (Switchable Controls)	<input checked="" type="checkbox"/>
Ride Control	<input checked="" type="checkbox"/>
Horn	<input type="checkbox"/>

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.